

## Features

- Up to 18 personal memory slots
- Protect up to 10 messages
- Individual message delete or delete all
- Backlight
- Private time
- Daily alarm
- Time and date display
- Time and date message stamping
- Alert types: Melody, Chirp, Vibration, Vibration-chirp, Silent
- Battery level indicator
- Battery low indicator and alert
- Out-of-range indicator and alert
- Unread message reminder alert
- Duplicate message indication
- Continuous message indication
- Error message indication
- Memory full indication
- Memory retention

## Top Mount Synthesized POCSAG Numeric Pager



## Specifications

Model no.	Br502		
Frequency:	VHF (135-175MHz), UHF (452-468MHz) 900MHz (929-932MHz)		
Code Format:	31/21 POCSAG Code		
Channel Spacing:	12.5 kHz, 25 kHz		
Frequency Deviation:	± 2.5 kHz, ± 4.5 kHz		
Paging Sensitivity:	VHF/UHF	900MHz	(c.f. 22.5dB)
	-107 dBm	-104 dBm	
EIA Selectivity:	55 dB @ +/-25kHz	40 dB	
EIA Spurious and Image:	50 dB	40 dB	
IMRejection:	50 dB	40 dB	
OperatingTemperature:	-10°C to 50°C	5°C to 40°C	
AlertTone Loudness:	75 dB @ 12 inches		
BatteryType:	1 x Alkaline AAA		
Weight (with battery):	45 grams		
Dimensions:	64 x 43 x 19.5 mm		

