

## Features

- Up to 18 personal memory slots
- Protect up to 10 messages
- Individual message delete or delete all
- Backlight
- Private time
- Daily alarm
- Time and date display
- Time and date message stamping
- Alert types: Melody, Chirp, Vibration, Vibration-chirp, Silent
- Battery level indicator
- Battery low indicator and alert
- Out-of-range indicator and alert
- Unread message reminder alert
- Duplicate message indication
- Continuous message indication
- Error message indication
- Memory full indication
- Memory retention

## Top Mount Synthesized FLEX™ Numeric Pager



## Specifications

Model no.	Br502	
Frequency:	900MHz (929-932MHz), VHF (135-175MHz)	
Code Format:	FLEX, 1600/3200/6400 bps	
Channel Spacing:	25 kHz	
Frequency Deviation:	+/- 4.8 kHz	
Paging Sensitivity:	-104 dBm (c.f. 22.5dB)	
	900MHz	VHF
EIA Selectivity:	40 dB	50 dB
EIA Spurious and Image:	40 dB	50 dB
IM Rejection:	40 dB	50 dB
Operating Temperature:	5°C to 40°C	-10°C to 50°C
Alert Tone Loudness:	75 dB @ 12 inches	
Battery Type:	1 x Alkaline AAA	
Battery Life:	~70 days (collapse value=4)	
Weight (with battery):	45 grams	
Dimensions:	64 x 43 x 19.5 mm	



RAD DEV FOR HAZ LOC INT SAFE  
CI.I,Div1,Gr.CD, CI.I,Div2,Gr.ABCD, Exia, T4